



Slewing Drive Performance Data

Rated Output Speed	0.06RPM
Normal Output Torque	558 N.m
Tilting Moment Torque	1500 N.m
Holding Torque	5800 N.m
Axial Rating	10kN
Radial Rating	15 kN
Slewing Drive Ratio	31: 1
Tracking Precision	$\leq 0.1^\circ$
IP(Class)	66
Efficiency	40%
Temperature	-40°C to +120°C

Reducer Motor Performance Data

Rated Voltage	24VDC
Rated Current	<5
Output Power	30W
Output Speed	2RPM
Output Torque	45N.m

DESIGNED BY	Tommy 2022.08.29
CHECKED BY	Jonson 2022.08.29
APPROVED BY	Tony 2022.08.29

Startak ApS
 www.startaksolar.com

ALL PROPRIETARY RIGHTS IN THE SUBJECT MATTER HEREOF ARE RESERVED AND NO PERMISSION IS GRANTED TO REPRODUCE THIS PRINT IN WHOLE OR IN PART, OR TO DISCLOSE ANY OF THE INFORMATION TO OTHERS.

WEIGHT	SCALE
32Kg	1:3

SLEWING DRIVE

SYMBOLS ISO	SIZE	A3	SHEET	1/1
			THE TOLERANCE NOT MENTIONED IS REFERRED TO ISO2786-vL,CASTING TOLERANCE ISO 8062-CT10	

RD3A

REV
A